

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://reepack.nt-rt.ru/> || rkf@nt-rt.ru

Reepack ReeMaster 800



CHARACTERISTICS

Type

linear array

Operational mode

automatic

Other characteristics

for the food industry, vacuum, with modified atmosphere packaging

DESCRIPTION

Machine suitable with wider die than the RMR600 so that it can process large batches. An intuitive HMI touch screen controller makes every operation easy. One or two-tracks inline trays can be configurable and a positioning system TPS (Patented Reepack) allows to pack up to 6 trays in two lines. The die is loaded and unloaded by trays with an automatic transfer done by suitable grippers which lock the trays. The grippers movement is precisely defined in HMI and due to the servo motor drive ensure a secure transfer of filled trays. Finally an automatic discharge double belts with differenced speed allows the tray output in one line at the time, suitable for labelling and weighing. A wide range of equipments to add in options allow the RMR 800 to be easily integrated in a food processing line. The IN-LINE design allows 360° access to all machine components and tooling, allowing easy maintenance and cleaning. Stainless steel washdown construction providing the highest level of sanitization.

Available for M.A.P and Vacuum Skin packages with preformed trays of almost any size, quality or shape.

Machine height: 1900 mm

Machine width: 1250 mm

Machine Length: 4700 ÷ 7700 mm

infeed conveyor length: 2000÷ 5000 mm

Length free loading area: 1300 ÷4300 mm

No. of trays to load: 3÷25

Height free loading area: 920 ÷ 980

Machine main movments: Servo-drivers

Microprocessor Control: PLC-Siemens

Control panel: Touch screen

Vacuum Pump: 200 - 300 - 600 m3/ h

Electrical supply: 3/N/PE 400V AC 50Hz

Electrical consumption: 30kW

Compressed Air: S=0 MAP=0

Overall construction: Stainless Steel