

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Ижевск (3412)26-03-58
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://reepack.nt-rt.ru/> || rkf@nt-rt.ru

ReeFlow 100HS, ReeFlow 100W



CHARACTERISTICS

Operational mode

automatic

Product applications

for food products

Other characteristic

with shrink tunnel

Width

1,460 mm

(57.5 in)

Length

4,370 mm

(172 in)

DESCRIPTION

Hygienic, flexible and user friendly.
The industrial solution for non stop production.:

Main features:

- Full Stainless steel cantilevered construction with 'open frame' frame design easy to access and clean.
- Robust lugged infeed with fast and simple pitch changeover.
- Driven reel shaft for film width 650 mm. Automatic film tensioning to process efficiently most of materials.
- Standard photocell 'No product No bag', no more film waste.
- x3 independents pairs of rollers, for for best longitudinal sealing quality. . (C- H- F)
- Rotative 250mm jaws, production speed up to 120 ppm (400 ppm with VHS multiple jaws), fast and accurate. - Product discharge through 900 mm driven belt with adjustable small nose roller.
- Schneider platform with friendly touch screen 10 "coloured display: Functional and Easily operated.
- Full servo driven solution with 4 axis - Automatic format change and finest tuning.

Made in compliance with the standard requirements of the fresh food industry.

Film reel mounting position: Top

Longitudinal sealing position: Bottom

Transversal sealing system: Rotative motion

Outfeed conveyor length: 825 mm

Power supply: 400V 3N/PE 50/60 Hz

Power consumption: Up to 16 Kw

Compressed air: 6 bar - 16 NL (per cycle)

Bag width: Up to 250 mm

Bag length: Up to 600 mm

Max. product height: 150 mm

Sealing width: 15 mm

Human Interface: 7" colored touch-screen panel

Fixed/ Adjustable Folding Boxes

Printed Film Mark

Gas flushing system

Different sealing texture/width

Zig-Zag cut for easy-opening

Euro/Circular Hole